



OC810-ADT

The OC810 is a Pulse compatible outdoor camera with night vision. It can be used as a wireless camera using Wi-Fi connectivity.

OC810-ADT

OC810-ADT



Manual

[OC810-ADT Wireless Outdoor Day/Night Camera Installation Manual](#)

Reset

The reset button has two functions:

- **Reboot** – If your camera is unresponsive or is encountering technical issues, you may need to reboot your camera. To reboot, press and release the Reset button.
- **Clear All Data** – If rebooting your camera does not resolve the issue or if you need to re-enroll your camera to Pulse, you may need to clear all data. To clear all data and restore the factory default settings:
 1. Power on the camera
 2. Press and hold the Reset button for eight seconds
 3. When you release the Reset button, the camera is reset to the factory default settings

Troubleshooting	<ul style="list-style-type: none"> • Wi-Fi Camera Offline – Please refer to this page if your Wi-Fi is not connected and is listed as “status unknown” in the ADT Pulse app. • Camera Video Quality – Please refer to this page if you are encountering issues with your camera’s video quality. • Pulse Gateway Offline – The video gateway controls your wireless connections. Please refer to this page if your device is offline or is receiving a “Status Unavailable” message.
Specifications	<ul style="list-style-type: none"> • Dimensions: 3.70" (W) x 4.06" (H) x 1.46" (D) • Operating Temperature: 14°F to 113°F • Storage Temperature: -4°F to 158°F • Weather Resistance: IP 65 • Network Interface: TCP/IP, HTTP, HTTPS, DHCP, SMTP, FTP, UPnP, DDNS, NTP, RTP, RTCP, RTSP, SMB • Wireless Interface: IEEE 802.11n/892,11b/802.11g compatible, Infrastructure/Ad-Hoc mode, WEP/WPA Personal/WPA2 Personal security support, roaming support • LEDs: 1 indicator LED and 8 IR LEDs • Illuminator: Night range approximately 25 feet • Power Adapter: Input: 100-240 VAC; Output: 12V/1A
Communication	This camera can use Wi-Fi to connect to Pulse, or it can be hardwired directly to the gateway or switch using the provided adapter.
Pulse Enrollment	This camera can be enrolled through the Manage Device section of the Web or Admin Portal. This device must be paired to Pulse while it is wired to the gateway using the provided adapter. For help enrolling your camera, please refer to the Pulse Camera Add On and Replacement page.

Return to Top